

ALT5000M-E

[Home](#) [Product](#) [Lighting Towers](#) [ALT5000M-E](#)



Product model: ALT5000M-E

Lighting power: 4x400W

Dimension (fully retracted): 1505×895×2218 mm

Dimension(fully extended): 1651x1868x5068 mm

Engine model: PL186FADE

Controller: Key start

[Specifications download](#)

[Brochure download](#)

Basic parameters	
Dimension (fully retracted): mm	1505×895×2218
Dimension(fully extended): mm	1651x1868x5068
Weight: kg	258
Maximum towing speed: km/h	5km/h
Maximum wind speed rating km/h	35km/h
Voltage (50HZ) V	240V
Voltage (60HZ) V	
Ampere (50HZ) A	20.8A
Ampere (60HZ) A	

Engine / Alternator	
Rated output KVA/KW	5KVA/4KW
Engine brand	POWERLINK

Engine model	PL186FADE
Frequency HZ	50
Speed RPM	1500
No. of cylinders	4
Engine aspiration	Natural aspiration
Alternator insulation	H
Lighting power kw	4x400W
Mast extension	Manually
Lighting tilt	Manually
Stabilizing Legs	Manually
Mast rotation	N/A
Protection class	IP23
Noise level @7m DBA	74dB(A)
Controller	Key start

Navigation

[Home](#)

[Why PowerLink?](#)

[Solution](#)

[Product](#)

[Service & Parts](#)

[Community](#)

[Support](#)

Diesel Generator Sets

[50HZ Diesel Generator Sets](#)

[60HZ Diesel Generator Sets](#)

[Specialized market for Genset](#)

[Diesel Generator Sets Solution](#)

[Service & Parts](#)

Gas Energy Products

[Gas Generator Sets](#)

[Cogeneration Sets](#)

[Supporting equipment](#)

[Gas Energy Solution](#)

[Data Download](#)

Air Compressors

[Portable Compressors](#)

[Motor Driven Compressors](#)

[Diesel Driven Compressors](#)

[Air Treatment](#)

[Air Compressors Solution](#)